

Option List

9/12/2022

Customer: Williamstown - Kentucky
Representative
Organization:
Requirements Manager:
Description: Williamstown - Commercial Pumper / Tanker - Eric
Body: Pumper, Long, Aluminum, 2nd Gen, Commercial
Chassis: International HV607, 4x2, Single Rear Axle

Bid Number:
Job Number:
Number of Units: 1
Bid Date:
Stock Number:
Price Level:
Lane:

Line	Option	Type	Option Description	Qty
			Build-to-Order, Boiler Plates, Pumper, w/Commercial Chassis	1
			Fire Department/Customer - Williamstown Fire Department Operating/In conjunction W-Service Center - Operating Miles - 75 Miles	1
			Bidder/Sales Organization - Delivery - Delivery representative Dealership/Sales Organization, Service - Service Centers and Mobile Techs	
			Commercial chassis & Snorkel products	1
			Manufacture Location-	1
			Vehicle Destination, US	1
			Comply NFPA 1901 Changes Effect Jan 1, 2016, With Exceptions, Commercial Chassis	1
			Pumper/Pumper with Aerial Device Fire Apparatus	1
			Vehicle Certification, Pumper	1
			Agency, Apparatus Certification, Pumper/Tanker, Third Party, PMFD Inspection Trip(s)	1
			A Final Inspection trip shall be provided for 3 members of Williamstown to travel to Factory. All meals, travel, and rooms will be covered.	
			Unit of Measure, US Gallons	1
			Bid Bond, 10%	1
			Performance Bond, Not Requested	1
			Approval Drawing	1
			Electrical Diagrams, Commercial	1
			International HV607, 4x2, Single Rear Axle	1
			Model Year 2025	1
			Base Price, International HV607, 4x2, Effective 07/01/2022	1
			Wheelbase, 241" thru 311", International HV 4x2	1
			Wheelbase - 248.5	
			GVW Rating, Commercial Chassis	1
			GVW rating - 45,000	
			Frame, Chassis, International	1
			Frame Reinforcement, International HV 4x2, "C" Channel	1
			Axle, Front, 14K Rating, International MV/HV	1
			Suspension, Front Spring, 14,600 lb, Commercial	1
			Shock Absorbers, Front	1
			Brakes, Cam Front, 16.50"x 5.00" Commercial	1
			MichelinTires	1
			Tires, Front, 12R22.50	1
			Wheels, Polished Aluminum, 22.50" x 8.25"	1
			Axle, Rear, 26K Rating, Dana Spicer, International MV/HV	1
			S-Cam Style 16.50" x 7.00"	1
	SP		Top Speed of Vehicle, Commercial Chassis, New Top Speed Programming	1
			Top Speed of Vehicle - 73 to 75	
			Suspension, Rear Spring, 31,000 lb, Commercial	1
			Tires, Rear, 12R22.50	1
			Wheels, Polished Aluminum Outer w/ Steel Inner, 22.50" x 8.25"	1

Line	Option	Type	Option Description	Qty
			Tire Pressure Monitoring, RealWheels, AirSecure, Valve Cap, Single Axle	1
			Qty, Tire Pressure Ind - 6	
			Axle Hub Covers w/center hole, Real Wheels Brand, S/S, Front Axle	1
			Axle Hub Covers, Rear, S/S, High Hat (Pair)	1
			Covers, Lug Nut, Chrome	1
			Mud Flap, Front and Rear, Pierce Logo	1
			Chocks, Wheel, SAC-44-E, Folding	1
			Qty, Pair - 01	
			Mounting Brackets, Chocks, SAC-44-E, Folding, Horizontal	1
			Qty, Pair - 01	
			Location, Wheel Chocks - Left Side Rear Tire, Forward, LS3	
			ABS, Anti-Lock Braking System, Commercial	1
			Air Compressor, Brake, 18.7 CFM, Commercial	1
			Air Dryer, Brake, w/Heater, Commercial	1
			Air Inlet, w/Disconnect Coupling, Commercial Chassis	1
			Location, Air Coupling(s) - h) DS Pump Panel	
			Drain, Manual Air Tank w/Pull Cable (Commercial), Pierce Installed	2
			Qty, Man. Moist Ejector - 2	
			Engine, Cummins L9, 360 hp, IHC HV 4x2	1
			High Idle w/Electronic Engine, Commercial	1
			Auxiliary Brake, Engine Compression Brake, With Brake Lights, Commercial	1
			Fuel/Water Separator, Racor, International	1
			Air Intake, Engine, w/Ember Separator, OEM Installed, Commercial	1
			Exhaust System, Horizontal, RH Step Mounted DPF/SCR, Commercial	1
			Exhaust Modifications, Commercial Chassis, Horizontal Exhaust	1
			Coolant Hoses, Rubber - Commercial Chassis	1
			Fuel Tank, 50 Gallon, Left Side, Aluminum, Commercial	1
			DEF Tank, Left Side Location, Commercial	1
			Fuel Priming Pump, Electronic, Automatic, Cummins, No Swt Req'd	1
			Not Required, Shutoff Valve, Fuel Line	1
			Cooler, Chassis Fuel, Commercial, Provided by Chassis OEM	1
			Trans, Automatic, Allison 3000 EVS, w/(2) PTO Provsions, Commercial	1
			Transmission,Stalk Shifter, Column Mounted, 5 Speed, International	1
			Transmission Oil Cooler, Internal, Commercial	1
			Driveline for Mid-Ship Pump Installation - Provided By Chassis Mfgr - Commercial	1
			Steering, Power, w/Tilt Column, Commercial Chassis	1
			Bumper Extension, 19", Commercial Chassis	1
			Tray, Hose, Center, 19" Bumper, Outside Air Horns	1
			Grating, Bumper extension - Grating, Rubber	
			Capacity, Bumper Tray - 52) 100' of 2.00"	
			Cover, Aluminum Treadplate, One (1) D-Ring Latch, Hose Tray	1
			Stay arm, Tray Cover - b) Pneumatic Stay Arm	
			Tow Eyes, Chrome, Extended Out Front of Bumper	1
			Standard Hood, SBA, International	1
			Cab, 4-door Crew Cab, International HV	1
			Cab Interior, IHC, Gray	1
			Grille, Chromed Plastic, Stationary, International	1
			Mirrors, Bright Finish Heads, Power Adjust, Heated, International MV/HV	1
			Step Pkg, Deluxe Alum 4-Way w/Fuel Tank Cover, International MV/HV 4-Door	1
			Compartment, Storage/Tool, Under Right Crew Cab	1
			Lights, Cab & Crw Cab Acs Stps, P25, LED, 8Lts	1
			Power Windows & Door Locks, 4-Door Cab, Commercial	1
			Daytime Running Lts, Commercial	1
			Air Conditioning, Commercial	1
			Ember Screen, for AC Filter, Air Intake, International	1
			Lights, Engine Compt, (2) Commercial Chassis	1
			Console, IHC MV/HV Four (4) Door, Radio/Siren/Switches/Storage	1
			Seating Capacity, Cab, 4-Door, Commercial	5
			Qty, - 05	
			Seats, Air driver & fixed SCBA Officer - International MV/HV	1
			Seats, 3-man Seats Inc 911, w/SCBA - International	1

Line	Option	Type	Option Description	Qty
			Bracket, SCBA, Air Bottle, Hands-Free II, Cab Seats, Commr Cab	4
			Qty, - 04	
			Seat Belt Web Length, Commercial Chassis	1
			Seat Belts, Red, Commercial Chassis	1
			Helmet Storage, Provided by Fire Department, NFPA 2016	1
			Handlights, (4) Streamlight, Fire Vulcan, 44451, C4 LED, Tail Lts, 12v, Orange	1
			Location, Lights - TBD	
			Cab Instrumentation, Commercial Chassis	1
			Panel, Emergency Switch, Located In Floor Mt'd Console	1
			Light, Do Not Move Apparatus, Commercial Chassis	1
			Alarm, Do Not Move Truck - Steady Alarm	
			Light, Open Door - Commercial Std	1
			Wiper control, intermittent feature Commercial	1
			Wiring, Spare, 20 A 12V DC, 12 Circuit Fuse Block, Blue Sea 5026 1st	1
			Qty, - 01	
			12vdc power from - Battery direct	
			Location - Rear Console	
			Wiring, Spare, 37.5 A 12V DC, Cust Install Radio, 30A Bat Dir, 7.5A Ign & Grnd	1
			Qty, - 01	
			Location - Center Overhead Console	
			Wiring, Spare, 15 A 12V DC 1st	2
			Qty, - 02	
			12vdc power from - Battery direct	
			Wire termination - Butt Splice	
			Location, Spare Wiring - Officer Dash and Center Console	
			Wiring, Spare, 2.0 A 12V DC, USB Termination Blue Sea 1016 1st	2
			Qty, - 02	
			12vdc power from - Battery direct	
			Location - rear of Console	
			Radio, AM/FM Stereo, w/Weather Band & Clock,USB and Aux Input, International	1
			Speakers, AM/FM Radio - Standard Speakers with Radio System	
			(Commercial)	
			Not Available, Vehicle Information Center, Multiplex System, Commercial Chassis	1
			Collision Mitigation, Not Requested	1
			Vehicle Data Recorder w/Seat Belt Monitor, Commercial	1
			VDR Primary Inputs - No Primary Input	
			VDR Additional Input - No Additional Input	
			Intercom, Firecom 5100D Single Radio, 5-Pos, D,O,3C	1
			Location - in dash near department radio	
			Location, Intercom, C Cab - 3) 3 forward facing seats	
SPC			Cable, Radio to Intercom Interface, Firecom, 1 Radio, Kenwood	1
			Headset, Firecom, FH-51 Over Head, Radio Transmit	5
			Qty, - 05	
			Location, Headset - Driver Seat, Officer Seat, DS Inbrd, Fwrd Fcng Seat,	
			DS Outbrd, Fwrd Fcng Seat and PS Inbrd, Fwrd Fcng Seat	
			Hangers For Headsets, NFPA, Each	5
			Qty, - 05	
			Location, Headset Hangers - Driver Seat, Officer Seat, DS Outbrd, Fwrd	
			Fcng Seat, PS Outbrd, Fwrd Fcng Seat and Rear, Center, Fwrd Fcng Seat	
			Antenna Mount, Commercial Chassis, Cable Routed to Console	1
			Qty, - 01	
			Camera, Pierce, 7" LCD, Rear Camera Only	1
			Location, Camera Monitor - Driver Side Dash	
			Recess, Rear Vision Camera	1
			Location, Camera, Recessed - Center Rear	
			Electrical System, International Chassis	1
			Electrical System, International HV	1
			Single Start, (3) Grp 31, 660 CCA each, Ext/Crew Cab, International	1
			RELOCATE BATTERIES	1
			Battery Location, Top of Crew Cab Step Compartment, Left Side	1
			Selector, Single Start Battery, Commercial Chassis	1
			Battery Charger/Converter, Progressive Dynamics PD2180, 80A	1

Line	Option	Type	Option Description	Qty
			Location, Charger, Front Left Side Body Compartment	1
			Location, Battery Chrgr/Cmpr - High On Left Wall	
			Not Required, Remote Battery Charger Indicator	1
			Shoreline, 20A 120V, Kussmaul Auto Eject, 091-55-20-120, Super	1
			Qty, - 01	
			Color, Kussmaul Cover - d) yellow	
			Shoreline Connection - Battery Charger	
			Shoreline Location, Commercial Chassis/PMFD	1
			Location, Shoreline(s) - DS Pump Panel	
			Alternator, 325 amp Leece-Neville, International	1
			Load Manager, Kussmaul 2 Channel	1
			Cab Lighting, LED Clearance/Marker/Fender Turn Signals, International HV	1
			Light, Directional/Marker, Intermediate, Weldon 9186-8580-29 LED 2lts	1
			Lights, Clearance/Marker/ID, Rear, FRP LED Bar & P25 LED 4Lts	1
			Lights, Tail, WIn M62BTT* Red Stop/Tail & M62T* Amber Dir Arw For Hsg	1
			Color, Lens, LED's - Clear	
			Flash Pattern, Directional Lts - Steady On (Arrow)	
			Lights, Backup, WIn 600, LED for WIn Cast 3 & 4 housing	1
			Bracket, License Plate & Light, P25 LED	1
			Bezels, WIn, (2) M6 Chrome Pierce, For mtg (4) WIn M6 lights	1
			Alarm, Back-up Warning, PRECO 1040	1
			Lights, Perimeter Cab, Amdor AY-LB-12HW012 LED 4Dr	1
			Lights, Perimeter Pump House, Amdor AY-LB-12HW020 LED 2lts	1
			Lights, Perimeter Body, Amdor AY-LB-12HW012 LED 2lts, Rear Step, Comm Chassis	1
			Control, Perimeter Lts - Parking Brake Applied	
			Lights, Step, P25 LED 4lts, Pump Pnl Sw	1
			Light, Visor, FRC, 12V SPA851-Q15-* LED, Brow Mt, Commercial, 1st	1
			Switch, Lt Control 1 DC,1 - a) DS Switch Panel	
			Switch, Lt Control 2 DC,2 - e) No Control	
			Color, FRC/Rom Lt Housing - FRC, White Chrome Face	
			Lights, HiViz FT-GESM* LED 1st	2
			Location - DS front and rear side sheet	
			Qty, - 02	
			Control, Scene Lts - Cab Sw Panel DS and Pump Panel Sw LS	
			Color, Lt Housing HiViz - Crm Opt Hold, Crm Bez, Wht Fix	
			Lights, HiViz FT-GESM* LED 2nd	2
			Location - RS front and rear on side sheet	
			Qty, - 02	
			Control, Scene Lts - Cab Sw Panel DS and Pump Panel Sw LS	
			Color, Lt Housing HiViz - Crm Opt Hold, Crm Bez, Wht Fix	
			Lights, HiViz FT-GESM* LED 3rd	2
			Location - rear, high, one each side	
			Qty, - 02	
			Control, Scene Lts - Cab Sw Panel DS and Pump Panel Sw LS	
			Color, Lt Housing HiViz - Crm Opt Hold, Crm Bez, Wht Fix	
			Not Required, Deck Lights, Other Hose Bed & Rear Lighting	1
			Lights, Hose Bed, Sides, Dual LED Light Strips	1
			Control, Hose Bed Lts - Cup Switch At Rear	
			Lights, Not Required, Rear Work, Alt. 12 Volt Lights At Rear Body	1
			Lights, Walk Surf, FRP Flood, LED	1
			Pumper, Long, Aluminum, 2nd Gen, Commercial	1
			No Value Discount Available	1
			Tank, Water, 1000 Gallon, Poly, Long	1
			Overflow, 4.00" Water Tank, Poly	1
			Foam Cell Required	1
			Modified Poly Tank & Cradle, Ext'd To Rear, Pumper	1
			Notch, Poly Tank, Hose, Hydraulic Lines or Wiring	1
			Sleeve, Through Tank	2
			Qty, Sleeve - 2	
			Water Tank Sleeve - Plumbing/Hydraulic Diameter - 3" Plumbing	
			Restraint, Water Tank, Heavy Duty, Special Type Tank, 4x4, or Export	1
			Not Required, Direct Tank Fill	1

Line	Option	Type	Option Description	Qty
			Tank Fill, Direct, Rear, 4.00" Fireman's Friend	1
			Qty, - 1	
			Location, driver's/passenger's/center - Right	
			Adapter, Elbow - 4.0"NST x 5.0" Storz/2.5"x MNST w/Cap	
			Not Required, Dump Valve	1
			Not Required, Jet Assist	1
			Not Required, Dump Valve Chute	1
			Not Required, Switch, Tank Dump Master	1
			Hose Bed, Aluminum, Pumper	1
			Hose Bed Capacity, Special	1
			Capacity, Hosebed - 300' of 2" // 800' of 5" // 200' of 2.5"	
			Divider, Hose Bed, .25" Unpainted	2
			Qty, Hosebed Dividers - 2	
			Hose Restraint, Hose Bed, Velcro Strap on Top, 2" Heavy Nylon Web at Rear	1
			Type of fastener - Velcro straps	
			Nylon Web Color - Black	
			Type of fastener, Rear - seat belt buckle - bottom of hosebed	
			Cross-Divider, Hose Bed	1
			Running Boards, 12.75" Deep	1
			Tailboard, 16" Deep	1
			Wall, Rear, Smooth Aluminum/Body Material	1
			Material, Rear Wall Inboard Facing Surfaces - Aluminum Diamondplate	
			Tow Bar, w/Hitch Receiver, Sides Under Body	1
			Hose Restraint, Running Board, Velcro Straps	2
			Location, Hose Tray, Running Board - a) both sides	
			Qty, Tray, Hose - 2	
			Tray, Hose, Running Board, Soft Suction Hose, 25' of 5.00"	2
			Location, Hose Tray, Running Board - a) both sides	
			Qty, Tray, Hose - 2	
			Punched Pattern, Star, Tailboard	1
			Construction, Compt, Alum, Pumper	1
			LS 171" Rollup, Full Height Front & Rear, FDLER	1
			RS 171" Rollup, Full Height Front & Rear, FDLER	1
			Doors, Rollup, Gortite, Side Compartments	6
			Qty, Door Accessory - 06	
			Color, Roll-up Door, Gortite - Painted to Match Lower Body	
			Latch, Roll-up Door, Gortite - Non-Locking Liftbar	
			Compt, Rear, Rollup, 37.75" FF, 25.88" D	1
			Door, Gortite, Rollup, Rear Compartment	1
			Color, Roll-up Door, Gortite - Satin finish	
			Latch, Roll-up Door, Gortite - Non-Locking Liftbar	
			Guard, Drip Pan, S/S, Rollup Door	7
			Qty, Door Accessory - 07	
			Location, Door Accessory - LS1, LS2, LS3, RS1, RS2, RS3, and rear	
			Lights, Compt, Pierce LED, Dual Light Strips, Each Side of Door, Pumper/Tanker	5
			Qty, - 05	
			Location, Compartment Lights - All Body Compts	
			Shelf Tracks, Painted	7
			Qty, Shelf Track - 07	
			Location, Shelf Track - LS1, LS2, LS3, RS1, RS2, RS3 and B1	
			Shelves, Adj, 500 lb Capacity, Full Width/Depth, Predefined Locations	8
			Qty, Shelf - 08	
			Material Finish, Shelf - Painted - Spatter Gray	
			Location, Shelves/Trays, Predefined - LS1-Transition Point, RS1-Transition Point, RS3-Transition Point, RS3-Lower Third, RS3-Upper Third, RS1-Upper Third, LS3-Upper Third and LS3-Transition Point	
			Tray, Floor Mounted, Slide-Out, 500lb, 2.00" Sides	4
			Qty, - 04	
			Location, Tray Slide-Out, Floor Mounted - RS1, RS3, LS1 and LS3	
			Material Finish, Tray - Painted - Spatter Gray	
			Toolboard, Swing-out, Alum, .188", Peg Board	1
			Qty - 1	
			Location, Pivot - Back	

Line	Option	Type	Option Description	Qty
			Mounting, Toolboard - Stationary	
			Hole Diameter, Pegboard/Toolboard - .281" diameter	
			Finish, Pegboard/Toolboard - Painted - Spatter Gray	
			Location, Toolboard - LS2	
			Rub Rail, Aluminum Extruded, Side & Rear of Body	1
			Fender Crowns, Rear, Stainless, w/Removable Liner	1
			Material Finish, Fender Liner - Painted Lower Body	
			Not Required, Hose, Hard Suction	1
			Trough, HSH, (1), Compartment Top Mount	2
			Qty, - 02	
			Location, Hose Trough/Compartment - l) one each side	
			Trough, Material - Alum - Painted	
			Trough, Latch Type - clamps	
			Handrails, Side Pump Panels, Per Print	1
			Handrails, Beavertail, Standard	1
			Handrail, Rear, Below Hose Bed, Full Width	1
			Compt, Extinguisher (2) Fender Panel, Triangular Door	1
			Location, Bracket/comp. - on the right side behind of the rear wheels -	
			RS Rear	
			Qty, - 1	
			Door Finish, Fender Compt - Polished	
			Latch, Air Bottle Compt - Southco C2 Chrome Raised	
			Insert, Air Bottle Compt - Rubber Matting	
			Compt, Air Bottle, Double, Fender Panel	3
			Qty, Air Bottle Comp - 3	
			Door Finish, Fender Compt - Polished	
			Location, Fender Compt - Double - LS Fwd, Double - LS Rear and	
			Double - RS Fwd	
			Latch, Air Bottle Compt - Southco C2 Chrome Raised	
			Insert, Air Bottle Compt - Rubber Matting	
			Ladder, 24' Duo-Safety 900A 2-Section	1
			Ladder, 16' Duo-Safety 875A Roof	2
			Qty, - 02	
			Ladders Btwn Tank & S.Sht, RS, Ext'd Rr, Encl'd Complete, RPH	1
			Material Trim/Scuffplate - a) 4-way alum, Bright	
			Door, Material & Finish, Ladder Storage - smooth aluminum	
			Latch, Door Ladder Storage - D-Handle latch	
			Hinge Location - Left Side	
			Ladder, 10' Duo-Safety Folding 585A, w/Mounting	1
			Location, Folding Ladder - Ladder Compartment	
			Pike Pole, Pumper, Provided by Dealer, Additional	3
			Location - in ladder storage compt	
			Qty, Pike Poles - 3	
			Pike Pole Make and Model - 6ft trash pole // 6ft dry wall // 10ft pike pole	
			Pike Pole, 8' Fire Hooks Unlimited, New York Roof Hook, Fiberglass, Pry End,RH-8	1
			Qty, - 01	
			Pike Pole, 6', Pumper, Provided by Fire Department, NFPA 2016	1
			Pike Pole Make/Model - Duo-Safety 6' Pike Pole	
			Tubes, Alum, Pike Pole Storage, Spcl Notch, NY PP Head	1
			Location - in ladder storage	
			Qty, Pike Pole Tubes - 01	
			Tubes, Alum, Pike Pole Storage	4
			Qty, Pike Pole Tubes - 04	
			Location, Pike Pole Tube - Ladder Storage	
			Steps, Folding, Front of Body, Cargo Bed Access, w/LED, Trident	1
			Coating, Step - black	
			Location, Steps - Full Height Left, One (1) Right Side w/LED Light	
			Steps, Folding, Rear of Body, w/LED, Trident	1
			Coating, Step - black	
			Step, Corner Step, Each	1
			Qty, - 1	
			Location - in the DS cargo	
			Pump House, Side Control, 48", Control Zone	1
			Pump House Structure, Raised, Included with Ladder Storage	1

Line	Option	Type	Option Description	Qty
			Pump, Waterous, CXC20, 1500 GPM, Single Stage, Midship Split Shaft	1
			Seal, Mechanical, Waterous	1
			Trans, Pump, Waterous C20 Series	1
			Pumping Mode, Stationary Only	1
			Pump Shift, Air Mnl Override, Split Shaft, Interlocked, Waterous	1
			Transmission Lock-up, EVS	1
			Auxiliary Cooling System	1
			Not Required, Transfer Valve, Single Stage Pump	1
			Valve, Relief Intake, Elkhart	1
			Qty - 1	
			Pressure Setting - 125 psig	
			Intake Relief Valve Control - Behind Right Side Pump Panel	
			Controller, Pressure, Pierce, Pump Boss, PBA300	1
			Primer, Trident, Air Prime, Air operated, w/(1) Additional Priming Valve	1
			Inlet Extra Primer - Front Inlet	
			Manuals, Pump, (2) Total, Electronic Copies	1
			Plumbing, Stainless Steel and Hose, Single Stage Pump, Control Zone	1
			Plumbing, Stainless Steel, w/Foam System	1
			Inlets, 6.00" - 1250 GPM or Larger Pump	1
			Valve, Ball Intake, TFT, AP Series	1
			Location - TBD	
			Qty - 1	
			Hand Wheel Shaft - Standard	
			Connection, Inlet, Side B - 8NX (6.0" Male Threaded Rigid) with a cap	
			Connection, Outlet, Side A - NX (6.0" Threaded Swivel)	
			Valve, Ball Intake, TFT, AX Series	1
			Location - TBD	
			Qty - 1	
			Hand Wheel Shaft - Standard	
			Connection, Inlet, Side B - 1ST (5.0" Rigid Storz) with a cap	
			Connection, Outlet, Side A - NX (6.0" Threaded Swivel)	
			Cap, Main Pump Inlet, Long Handle, NST, VLH	1
			Valves, Akron 8000 series- All	1
			Valve, Inlet(s) Recessed, Side Cntrl, "Control Zone"	2
			Qty, Inlets - 2	
			Control, Inlet, at Valve	1
			Inlet (1), Left Side, 2.50"	1
			Inlet, Right Side, 2.50"	1
			Inlet, 4" to 6" Front, 4" Plumbing, w/Bleeder Valve, Navistar/FLR	1
			Inlet, Size - Five	
			Drain, Suction - T Swing Handle	
			Control, Front Inlet, Electric, w/Indicator Lights	1
			Valve, Relief Intake, Front Inlet, Elkhart	1
			Pressure Setting - 125 psig	
			Swivel, Front Inlet, 4.00" to 6.00", w/Drain	1
			Inlet, Size - 5.00" Inlet	
			Inlet Bleeder - Quarter-Turn Style Bleeder	
			Finish, Front Inlet Elbow/Adapter - Chrome	
			Cap, Front Inlet, Long Handle, VLH	1
			No Rear Inlet (Large Dia) Requested	1
			No Rear Inlet Actuation Required	1
			Not Required, Cap, Rear Inlet	1
			No Rear Intake Relief Valve Required on Rear Inlet	1
			No Rear Auxiliary Inlet Requested	1
			Valve, .75" Bleeder, Aux. Side Inlet, "T" Swing Handle	1
			Tank to Pump, (1) 3.00" Valve, 3.00" Plumbing	1
			Outlet, Tank Fill, 1.50"	1
			Control, Outlets, Manual, Pierce HW if applicable	1
			Outlet, Left Side, 2.50"	2
			Qty, Discharges - 02	
			Elbow, Left Side Outlets, 45 Degree, 2.50" FNST x 2.50" MNST, VLH	1
			Not Required, Outlets, Left Side Additional	1

Line	Option	Type	Option Description	Qty
			Not Required, Elbow, Left Side Outlets, Additional	1
			Outlet, Right Side, 2.50"	1
			Qty, Discharges - 01	
			Elbow, Right Side Outlets, 45 Degree, 2.50" FNST x 2.50" MNST, VLH	1
			Not Required, Outlets, Right Side Additional	1
			Not Required, Elbow, Right Side Outlets, Additional	1
			Outlet, 4" w/4" Right, Handwheel	1
			Valve, Brand - Akron	
			Elbow, Large Dia Outlet, 30 Deg, 4.00" FNST x 5.00" Storz	1
			Qty, - 01	
			Outlet, Front, 1.50" w/2" Plumbing	1
			Fitting, Outlet - 1.50" NST with 90 degree swivel	
			Drain, Front Outlet - Automatic	
			Location, Front, Single - top of left bumper	
			Outlet, Rear, 2.50"	2
			Qty, Discharges - 02	
			Location, Outlet - c) one (1) each side	
			Elbow, Rear Outlets, 45 Degree, 2.50" FNST x 2.50" MNST, VLH	1
			Not Required, Outlet, Rear, Additional	1
			Not Required, Elbow, Rear Outlets, Large, Additional	1
			Not Required, Outlet, Hose Bed/Running Board Tray	1
			Caps/Plugs for 1.00" to 3.00" Discharges/Inlets, Chain	1
			Valve, 0.75" Bleeder, Discharges, "T" Swing Handle	1
			Outlet, 3.00" Deluge w/TFT Extend-a-Gun XG12	1
			Monitor, TFT Hurricane XFIH-D11A, 1250 GPM, Dual Handwheel	1
			Monitor Finish - Painted by OEM	
			Nozzle, TFT MST-4NJ Tips w/ XF-SS10 Shaper	1
			Deluge Mount, 3" ANSI 4 Bolt Flange	1
			Speedlay Module Not Required	1
			Hose Restraint Not Required, No Speedlay Module	1
			Speedlays, Not Required	1
			Speedlays, Not Required	1
			Crosslays Sngl Sheet Unpainted, (2+) 1.50", Std. Cap	2
			Qty, Crosslays - 2	
			Crosslays Sngl Sheet Unpainted, (1) 2.50" Std Cap, PMFD	1
			Hose Restraint, Crosslay/Deadlay, 1" Heavy Nylon Web, Strap Fasteners, Each Side	2
			Qty, - 02	
			Type of fastener - 1" cam buckle	
			Nylon Web Color - Black	
			Restraint Location - Bottom (towards the ground)	
			Not Required, Speedlays	1
			Hose Restr, Spdly, Not Required, No Spdly	1
			Hose Restraint, Crosslay/Deadlay, Aluminum Treadplate, Top Only	1
			Stay arm, Tray Cover - d) No Stay Arm	
			Restraint Location - Front (towards front of truck)	
			Crosslays, 8.00" Lower Than Standard - Control Zone w/9.00" Raised PH	1
			Foam Sys, Husky 3, Single Agent, Multi Select Feature	1
			Discharge, Foam Locations - Front Bumper Center, Crosslay Front, Crosslay Center and Crosslay Rear	
			Not Required, CAF Compressor	1
			Refill, Foam Tank, Integral, Husky 3	1
			Demonstration, Foam System, Dealer Provided	1
			Foam Cell, 30 Gallon, Not Reduce Water	1
			Type of Foam - Class "A"	
			Drain, 1.00", Foam Tank #1, Husky 3 Foam System, Quarter Turn	1
			Not Required, Foam Tank #2	1
			Not Required, Foam Tank #2 Drain	1
			Approval Dwg, Pump Panel(s), Not Required	1
			Pump Panel Configuration, Control Zone	1
			Material, Pump Panels, Side Control Black Vinyl	1
			Material Finish, Pump Panel, Side Control - Black Vinyl	
			Material, Pump Panel, Side Control - Aluminum	

Line	Option	Type	Option Description	Qty
			Panel, Pump Access - Vertical Hinged, Right Side, Hinged Left Side Gauge Pnl	1
			No Chassis Equipment/Pump House/Body Interference Identified,4Dr/2Dr Extd Cab	1
			Light, Pump Compt, WIn 3SC0CDCR LED White	1
			Qty, - 01	
			Gauges, Engine, Included With Pressure Controller	1
			Throttle, Engine, Incl'd w/Press Controller	1
			Indicator Light @ Pump Panel, Throttle Ready, Incl w/Pressure Gov/Throttle,Green	1
			Indicators, Engine, Included with Pressure Controller	1
			Indicator Light, Pump Panel, Ok To Pump, Green	1
			Control, Air Horn At Pmp Pnl, Button	1
			Discharge Bezels, Color Coded	5
			Qty, Gauges/Disc. - 05	
			Color, Discharge Tag - #1 Crosslay RED // #2 Crosslay BLUE // 2.5" Rear	
			Disc WHITE // Bumper Line PURPLE // LDDisc GREEN	
			Gauges, 6.00" Master, Class 1, 30"-0-600psi	1
			Gauge, 2.50" Pressure, Class 1, 30"-0-400psi	1
			Gauge, Water Level, Class 1, Remote Module Driver	1
			Activation, Water Level G - pg) pump in gear	
			Water Level Gauge, WIn PSTANK2, LED 1-Light, 4-Level, Use w/Pierce Class 1, Comm	3
			Qty, - 03	
			Location, Water Level Gauge, Single-Select - n) Body Sides & Rear	
			Activation, Water Level G - pg) pump in gear	
			Color, Trim - Chrome Housing	
			Gauge, Foam Level, (1) Tank, Class 1, GAAAR 5lt	1
			Light Shield, S/S LED	1
			Air Horns, (2) Hadley, 6" Round, eTone, In Bumper	1
			Location, Air Horns, Bumper, Each Side, Outside Frame, Outboard (Pos #1 & #7)	1
			Control, Air Horn, Lanyard Centered, Commercial Chassis	1
			Siren, WIn 295SLSA1, 100 or 200 Watt	1
			Location, Elect Siren, Console, Commercial	1
			Control, Elec Siren, Head Only	1
			Speaker, (2) WIn, SA315P, w/Pierce Polished Stainless Steel Grille, 100 watt	1
			Connection, Speaker - siren head	
			Location, Speaker, Frt Bumper, Recessed, Ea Side, Outside Frame, Inbrd (Pos 2/6)	1
			Siren, Federal Q2B	1
			Finish, Q2B Siren - Chrome	
			Siren, Mechanical, Mounted Above Deckplate	1
			Location, Siren, Mech - a) Left	
			Control, Mech Siren, Multi Select	1
			Control Mech Siren, Ft Sw LS	1
			Control Mech Siren, Ft Sw RS	1
			Sw, Siren Brake, Momentary Chrome Push Button, RS	1
			Not Required, Warning Lights Intensity	1
			Lightbar, WIn, Freedom IV-Q, 72", RRRRRRW__WRRRRRR	1
			Filter, Whl Freedom Ltbrs - No Filters	
			Lights, Front Zone, WIn M6** LED, Lens Choice, Commercial	1
			Flange Kit - w)with flange	
			Color, Lens, LED's - c)clear	
			Color, Lt DS Front - Red	
			Color, Lt PS Front - Red	
			Lights, Side Zone Lower, WIn M6*C LED, Clear Lens, 3pr, Ovr 25	1
			Location, Lights Front Side - b)each side bumper	
			Color, Lt Side Front - Red	
			Color, Lt Side Middle - Red	
			Color, Lt Side Rear - Red	
			Location, Lights Mid Side - Pump Panel	
			Location, Lights Rear Side - Rear Fender Panel	
			Lights, Rear Zn Lwr, WIn M6*C LED, Clear Lens, For Tail Lt Housing	1
			Color, Lt DS Rear - r) DS Rear Lt Red	
			Color, Lt PS Rear - r) PS Rear Lt Red	
			Light, Rear Zone Up, WIn L31HRFN LED Beacon, Red LED	1
			Color, Dome, Rear Warning - j) both domes clear	

Line	Option	Type	Option Description	Qty
			Not Required, Lights, Rear Upper Zone Blocking	1
			Mtg, Rear Warn Lts, On Top of Compt	1
			Light, Traffic Directing, WIn TAZ86, 30.87" Long TACTL5 Cnt LED	1
			Activation, Traffic Dir L - Not Connected	
			Location, Traf Dir Lt, Recessed with S/S Trim	1
			Location, Traf Dir Lt Controller, Center Console in Sw Pnl	1
			Receptacle Strip, 20A 120V 6-Place, Interior Body	2
			Qty, - 02	
			Location 1 - LS3 and RS3	
			AC Power Source - Inverter	
			Bag of Nuts and Bolts	1
			Qty, Bag Nuts and Bolts - 1	1
			NFPA Required Loose Equipment, Pumper, NFPA 2016, Provided by Fire Department	1
			Not Required, Soft Suction Hose	1
			No Strainer Required	
			Extinguisher, Dry Chemical, Pumper NFPA 2016 Class, Provided by Fire Department	1
			Extinguisher, 2.5 Gal. Pressurized Water, Pumper NFPA 2016, Provided by Fire Dept	1
			Axe, Flathead, Pumper NFPA 2016 Classification, Provided by Fire Department	1
			Axe, Pickhead, Pumper NFPA 2016 Classification, Provided by Fire Department	1
			Paint Process / Environmental Requirements, PMFD	1
			Paint, 90 Red, Commercial Grade Chassis Finish, PMFD Commercial Chassis	1
			Paint Color, Commercial, Std - #90 Candy Apple Red	1
			Chassis Cab Paint, #90 Red, by Chassis Manufacturer, Standard	1
			Paint Color, Commercial, Std - #90 Candy Apple Red	
			Paint, Two-Tone by International	1
			Paint Color, Commercial, Upper - #10 White	
			Paint, Chassis Frame Assy, Black, by Commerical Chassis Manufacturer Paint, Wheels, NOT REQUIRED - ALUMINUM WHEELS, Commercial Wheels, Accent Stripe NOT REQUIRED	1
			Compartment, Painted, Spatter Gray	1
			Reflective Band, 5"	1
			Color, Reflect Band - A - a) white	1
			Reflective across Cab Face	1
			Stripe, Chevron, Rear, Diamond Grade, Pumper	
			Color, Rear Chevron DG - fluorescent yellow green	1
			Stripe, Chevron, Bumper, 4" 2 colors, Diamond grade	1
			Color, Reflect Band - A - p) fluorescent yellow green diamond grade	
			Color, Reflect Band - B - z) red diamond grade	1
			Stripe, Reflective, Chevron, DG, Match Rear, Cab Drs Interior, Commercial, 4dr	
			Size, Chevron Striping - 04	
			Lettering Specifications, (GOLD STAR Process)	1
			Lettering, Printed Effect Gold Leaf, 3.00", (41-60)	
			Outline, Lettering - Outline	1
			Lettering, Printed Effect Gold Leaf, 4.00", (1-20)	1
			Outline, Lettering - Outline	1
STF			Turtle Tile	1
			Manual, Fire Apparatus Parts, USB, Body Parts Only, Commercial Product	1
			Manual on USB Flash Drive, Service, Commercial	1
			Manual, Commercial Chassis Operation	1
			Warranty, Basic, 1 Year, Apparatus, Commercial Chassis, WA0008	1
			Warranty, Basic Vehicle, 2 yrs, 100K Mile, International	1
			Warranty, Cab Paint, As Provided By Chassis Manufacturer, Commercial	1
			Warranty, Camera System, WA0188	1
			Warranty, LED Strip Lights, WA0203	1
			Warranty, 5-Year EVS Transmission, Standard Comm, WA0187 Warranty,	1
			Water Tank, Lifetime, UPF, Poly Tank, WA0195	1
			Warranty, Structure, 10 Year, Body, WA0009	1
			Warranty, Gortite, Roll-up Door, 6 Year, WA0190	1

Line	Option	Type	Option Description	Qty
			Warranty, Pump, Waterous, 7 Year Parts, WA0382	1
			Warranty, 10 Year S/S Pumbing, WA0035	1
			Warranty, Foam System, Husky 3, WA0231	1
			Warranty, Paint, 10 Year, Body, Pro-Rate, WA0057	1
			Warranty, Goldstar, 3 Year, Apparatus, WA0018	1
			Certification, Vehicle Stability, CD0156	1
			Certification, Cab Integrity, IHC, CD0025	1
			Amp Draw Report, NFPA Current Edition	1
			Amp Draw, NFPA/ULC Radio COMMERCIAL	1
			CHASSIS ENGINE, OTHER	1
			EVS 3000 Series TRANSMISSION	1
			WATEROUS PUMP- over like	1
			POLY TANK	1
			FOAM SYSTEM	1
			SIDE CONTROL	1
			AKRON VALVES	1
			ABS SYSTEMS, Commercial	1
			FRONT SUCTION	1
				1
				1
				1